



Karu Solar Floodlight

50W

Applications:

Residential and Commercial Applications.

- Lithium LFP Battery powered LED Solar Flood available in wattages of 50W, 100W & 200W.

- Die-Cast Aluminium body serving as an effective heatsink whilst providing added protection to the housing.

- 8m range controller with multiple setting selections. Timer for 3/5/8hrs usage or an Automatic Mode which will allow for 12hrs usage.

- 4-bar battery level indicator allowing you to see how much charge your battery has stored. The batteries can also be changed out at a later stage if required.

- 2m Standard Installation Cable with an additional 3m available as an accessory, ensuring your floodlights installation can be in even the most complex places.

- 21% efficiency Monocrystalline solar panels and 1.0mm² thick cable allowing for a faster charge with a longer lifespan, even in cloudy days.

- Lock/Unlock battery setting to preserve the battery during shipping and throughout its shelf-life.



Product Performance

Wattage	50W
Colour Temperature & Stock Code	• 6000K - FS001
Operating Temperature	-25~45°C
Life Span/ LB Rating	-
IP Rating	IP67
Beam Angle	90°
Impact Protection Grade	IK06
Input Voltage	4.5-6.5V
Surge Protection	-
CRI	>70
Lumen Output	500 Lumens
LED Chips	2835
LED Chips Qty	28
LED Chip Brand	Sanan
Dimmable	Yes by Remote Control
Dimmable Range	-
(Dali/Trailing/Leading)	-
UGR	-

Physical Characteristics

Weight (g)	918
Housing Material	Aluminum
Product Dimensions (mm)	161*223*51mm
Cable Length	100cm
Mounting Option	-
Bracket Material	Iron
Bolts and Screws	Stainless steel

[illegible]

Technical drawing of the front and side views of the 10000mAh Power Bank. The front view shows a rectangular device with a 4x6 grid of 24 status LEDs in the center. Dimensions are 161 mm (width), 144 mm (inner width), 223 mm (height), and 180 mm (inner height). The side view shows a thickness of 51 mm.

Technical Parameters	
Input Current	1.4A
Output Voltage	3V
Flicker(Y/N)	No Flicker
Humidity	0~35°C
Frequency	-
In Rush Current	-
Output Current	0.8A
THD	-
TA & TC	90&85
IES (Yes or No)	No
Regulatory Qualifications	
Class Rating	Class III
Energy Efficiency	A
Certification	CE, EMC, MSDS, UN38.3
Accessories	
Optional accessories	FS010 - 3M 1.0mm² Cable FS010-2 - 3M 1.0mm² Cable Ba2401 FS013 - Lithium LFP Battery 6A/3.2V 32700 x 1 for 50W
Packaging info	
Storage Temp	20~+45°
Carton Size (mm)	50.5*35.5*25.5
QTY/CTN	16
Net Weight	14,7
Gross Weight	16,6



Karu Solar Panel

7W

Applications:

Residential and Commercial Applications.

- Lithium LFP Battery powered LED Solar Flood available in wattages of 50W, 100W & 200W.

- Die-Cast Aluminium body serving as an effective heatsink whilst providing added protection to the housing.

- 8m range controller with multiple setting selections. Timer for 3/5/8hrs usage or an Automatic Mode which will allow for 12hrs usage.

- 4-bar battery level indicator allowing you to see how much charge your battery has stored. The batteries can also be changed out at a later stage if required.

- 2m Standard Installation Cable with an additional 3m available as an accessory, ensuring your floodlights installation can be in even the most complex places.

- 21% efficiency Monocrystalline solar panels and 1.0mm² thick cable allowing for a faster charge with a longer lifespan, even in cloudy days.

- Lock/Unlock battery setting to preserve the battery during shipping and throughout its shelf-life.

Product Performance

Wattage	7W (21% efficiency Monocrystalline solar panel)
Stock Code Code	FS001P
Operating Temperature	0~35°C
IP Rating	IP65
CRI	>70

Physical Characteristics

Weight (g)	690
Product Dimensions (mm)	180*270*16mm
Bracket Material	Iron
Bolts and Screws	Stainless steel
Output Voltage	6V
Flicker(Y/N)	No Flicker
Humidity	0~35°C
Output Current	1.4A
TA & TC	90&85
Energy Efficiency	A

Packaging info

Storage Temp	20~+45°
Carton Size (mm)	41.5*22.5*30
QTY/CTN	16
Net Weight	11,1
Gross Weight	12,8

Packaging



Dimension Drawing

