



LED 24V CV Driver

30W

PioLED Lighting (Pty) Ltd
031 701 5746
info@pioledlighting.africa

Product Performance

Wattage	30W
Colour Temperature & Stock Code	PS002a
Operating Temperature	-10 ~ 50°C
IP Rating	IP20
Input Voltage	185-265V
Surge Protection	1kV
Dimmable	No

Physical Characteristics

Weight (g)	90
Housing Material	Pure Aluminium
Product Dimensions (mm)	H 135 x L 35x W 23
Mounting Option	-

Technical Parameters

Input Current	0.28A
Output Voltage	24V
Humidity	20 ~ 99%RH, non- condensing
Frequency	50/60Hz
In Rush Current	Cold start 45A
Output Current	Max 1.25A
THD	≤1%
TA & TC	ta: -45°C tc: 85°C
IES (Yes or No)	No

Regulatory Qualifications

Energy Efficiency	A
Certification	IEC, CE

Packaging info

Storage Temp	-40°C ~ 80°C
Carton Size (mm)	37*29*22
QTY/CTN	100
Net Weight	11KG
Gross Weight	12KG

E&OE

PioLED Lighting (Pty) Ltd | 031 701 5746 | info@pioledlighting.africa

www.pioledlighting.co.za